# MILLER® ROPE GRABS & VERTICAL LIFELINES

Miller® rope grabs move easily up and down vertical lifelines to provide continuous fall protection. Trailing models offer complete handsfree operation for increased productivity. In the event of a fall, Miller® rope grabs lock quickly.

- · Compact design; corrosion-resistant stainless steel construction
- Lightweight and easy to use
- Certified to CSA standard Z259.2.1



Model	Mfg.		Price	
No.	No.	Description	/Each	
<b>SAK318</b>	8175/C	Stainless Steel Trailing Rone Grah For Use With 5/8" (16 mm) Rone		

Note: Locking snap hook - 3/4" (19 mm) gate opening.

#### **VERTICAL LIFELINES**

Honeywell

Model No.	Mfg. No.	Description	Price /Each
SC998	300L-Z7/25FTBL	5/8" dia. Copolymer Rope w/Snap Hook, 25'	
SC999	300L-Z7/50FTBL	5/8" dia. Copolymer Rope w/Snap Hook, 50'	

### **LIFTING YOKES &** SPREADER BARS • To be used with the harness equipped with

Nylon webbing Model No. SAR485 **Mfg. No.** FP4017B Price/Each \$



## **CARABINERS**

**Honeywell** 

- Twist-lock gates
- 400-lb. (181.4 kg) maximum capacity.

**SAK327** 





#### Honeywell <u>M</u>ILLER

Model No.	Mfg. No.	Material	Gate Opening "	Price/Each
SAK327	17D-1	Steel	1	
SAK328	17D-2-Z7/	Aluminum	1	
SAK330	18D-1	Steel	2	
SAK331	18D-2-Z7/	Aluminum	2 1/4	

### **ROPE GRABS & VERTICAL LIFELINES**

Rope grab and lifeline combinations still provide some of the most cost-effective solutions for fall protection needs. North offers you the widest assortment of rope implements in the market ranging from automatic rope grabs to rope adjusters.

- Constructed from quality, corrosion-resistant materials for long service life
  Match the device with the lifeline product that most suits your needs
- · Certified to CSA standard Z259.2.1





Model No.	Mfg. No.	Description	Price /Each
	C ROPE GRAB	νεχτήντου	/ Lacii
SN114	FP541	Automatic Panic Lock - Rope Grab	
SAG159	FP542	Automatic Panic Lock with 2' Lanyard, Energy Absorber with Snap Hook	

### **VERTICAL LIFELINES**

Model	Mfg.			Tensile	Price
No.	No.	Description	Composition	Strength	/Each
SN118	FP16E/PS50	5/8" (16 mm) 3-Strand, 50'	Copolymer Blend	8100 lbs. (3680 kg)	
SN119	FP16E/ <b>PS100</b>	5/8" (16 mm) 3-Strand, 100'	Copolymer Blend	8100 lbs. (3680 kg)	