

FOOT PROTECTION

BULLY

- Acid and oil-resistant Ultraflex™ compound
- Generous wider fit
- Self-cleaning outsole
- GelFlex fatigue resistant mid sole
- Slip resistant first impact heel strike design
- Also available in white



SAL023

RECOMMENDED APPLICATIONS:



Model No.	Mfg. No.	Size	Price /Each
STEEL TOE			
SAL013	9677-587-7	7	
SAL014	9677-587-8	8	
SAL015	9677-587-9	9	
SAL016	9677-587-10	10	
SAL017	9677-587-11	11	
SAL018	9677-587-12	12	
SAL019	9677-587-13	13	
STEEL TOE/STEEL PLATE*			
SAL020	9679-587-7	7	
SAL021	9679-587-8	8	
SAL022	9679-587-9	9	
SAL023	9679-587-10	10	
SAL024	9679-587-11	11	
SAL025	9679-587-12	12	
SAL026	9679-587-13	13	

Other sizes available

* Certified to CSA standard Z195

BLACKHAWK RUBBER BOOTS

- Made with lightweight thermoplastic rubber for better water resistance
- Features removable comfort made insole and self-cleaning outsole
- Material: Rubber
- Waterproof: Impermeable
- Certification(s) CSA/ASTM Approved



Model No.	Mfg. No.	Size	Price /Each
STEEL TOE/PLAIN SOLE			
SGG411	LICO-MT01-BK1-7	7	
SGG413	LICO-MT01-BK1-8	8	
SGG415	LICO-MT01-BK1-9	9	
SGG417	LICO-MT01-BK1-10	10	
SGG419	LICO-MT01-BK1-11	11	
SGG421	LICO-MT01-BK1-12	12	
SGG423	LICO-MT01-BK1-13	13	
SGG425	LICO-MT01-BK1-14	14	
SGG427	LICO-MT01-BK1-15	15	
STEEL TOE/PUNCTURE RESISTANT SOLE			
SGG388	LICO-MP01-BK1-7	7	
SGG390	LICO-MP01-BK1-8	8	
SGG392	LICO-MP01-BK1-9	9	
SGG394	LICO-MP01-BK1-10	10	
SGG396	LICO-MP01-BK1-11	11	
SGG398	LICO-MP01-BK1-12	12	
SGG400	LICO-MP01-BK1-13	13	
SGG402	LICO-MP01-BK1-14	14	
SGG404	LICO-MP01-BK1-15	15	

HAZMAX® 16" KNEE BOOTS

- Steel toe complies with ASTM F2413-11 and CSA Z195
- CSA Green Patch (sole protection and Grade 1 protective toe)
- Steel toe, steel shank and steel mid-sole for complete protection
- One-piece injection molded construction, eliminates seams
- Boots are constructed of high viscosity and flexible PVC alloy
- Non-absorbent polyester lining for easy cleaning and quick drying
- Replaceable cushioned insoles
- Cut off bands
- Kick off lug
- For use in situations involving dangerous chemicals, gasses or biological hazards and waste
- Exceeds CSA standards for dielectric footwear
- Certified by SEI to meet the requirements of NFPA 1991, 2005 edition



SC620



Model No.	Mfg. No.	Size	Price/Each
SC620	87012-6	6	
SC621	87012-7	7	
SC622	87012-8	8	
SC623	87012-9	9	
SC624	87012-10	10	
SC625	87012-11	11	
SC626	87012-12	12	
SC627	87012-13	13	
SAP837	87012-14	14	
SAP838	87012-15	15	

BOOT COVERS

12" LATEX HAZMAT

Made of 0.60 mm, high visibility yellow latex rubber, the Hazmat boot cover offers protection from a broad range of materials. Seamless covers provide a snug fit over existing footwear for an added layer of protection. The ribbed and textured sole provides traction on a variety of slippery surfaces. Strong enough to be worn many times, yet economical enough to be disposed of after a single use. 100% waterproof.

15" PVC BOOT/SHOE COVER

Made of a strong 0.20 mm PVC upper, heat-welded to a hard, embossed 0.50 mm PVC sole for superior slip resistance. Completely waterproof, equipped with an elastic top for easy pullover comfort and a secure snug fit. 100% waterproof.



SD638



Model No.	Mfg. No.	Size	Fits Size	Price /Each
12" LATEX HAZMAT				
SD588	97591-L	Large	7 - 9	
SD589	97591-XL	X-Large	10 - 12	
SAP794	97591-2X	2X-Large	13 - 16	
15" PVC BOOT/SHOE COVER				
SD636	97590-M	Medium	6 - 8	
SD637	97590-L	Large	9 - 11	
SD638	97590-XL	X-Large	12 - 14	

WHITE PVC STEEL TOE BOOTS

- Designed for use where mild chemical resistance is required
- Designed to help processing plants comply with HACCP guidelines
- Injected molded seamless construction
- Steel toe style complies with ASTM F2413-11
- Safety-Lok outsole
- Reinforced steel shank for added safety and comfort
- Replaceable cushion insoles
- Cut-off bands for height adjustment
- Pull-up and kick-off lugs for easy on and off
- Plain toe also available



SC573



Model No.	Mfg. No.	Size	Price /Each
SC573	81012-6	6	
SC574	81012-7	7	
SC575	81012-8	8	
SC576	81012-9	9	
SC577	81012-10	10	
SC578	81012-11	11	
SC579	81012-12	12	
SC580	81012-13	13	