

# MICROMETERS & CALIPERS

## ELECTRONIC DIGITAL MICROMETERS

- Large LCD display provides easy-to-read numbers
- Carbide tipped measurement surfaces
- Resolution to 5 decimal places
- Linear accuracy: +/- .0001" (.003 mm)
- Inch/millimetre conversion
- Includes calibration wrench
- Zero at any position
- Lock screw to hold mechanism in position
- Automatic OFF button
- Includes: (1) Thimble ratchet, (2) Type LR44 1.5 V batteries, (1) Plastic storage case with foam insert



**aurora tools**

Model No.	Measurement Range	Resolution	Price /Each
IA388	0-1" (0-25mm)	0.00005" (0.001mm)	

## ELECTRONIC CALIPERS

- Lightweight, ergonomic design
- Large easy to read LCD, 32" high
- Inch/millimeter conversion reads 0.0005" or 0.01 mm
- Zero at any position
- Automatic shut off after 5 minutes of nonuse
- Single long life battery is easily accessible
- Hardened stainless steel body
- Integrated depth rod on all sizes
- Fine adjustment thumb wheel
- Lock screw to hold the slide in position
- Resolution is 0.0005" (0.01 mm)
- Furnished in a fitted protective case



**Starrett**

Model No.	Mfg No.	Range	Approximate Jaw Depth	Price /Each
IA386	799A-6/150	0-6" (0-150mm)	1 1/2" (38 mm) Outside, 5/8" (16 mm) Inside	
IA379	EC799A-8/200	0-8" (0-200mm)	2" (50.8 mm) Outside, 3/4" (19 mm) Inside	

## DIAL CALIPERS

- Sharp, clear dial graduations of 0.001" with 0.100" per revolution
- Thumb-operated fine adjustment roll
- Sharp, black graduations on the satin finished bar, every 0.100"
- Lock screws for sliding jaw and dial bezel
- Covered rack depth rod 6" and 8" models
- Knife-edge contacts
- Adjustable bezel
- Hardened stainless steel bar, measuring surfaces, rack, gears and depth rod
- Positive, spring-loaded double pinion anti-backlash control



**Starrett**

Model No.	Mfg. No.	Description	Price/Each
HW273	1202-6	6" Dial Caliper w/Case	
HX214	1202-8	8" Dial Caliper w/Case	
HX215	3202-12	12" Dial Caliper w/Case	

## ALL STAINLESS STEEL ELECTRONIC DIGITAL CALIPERS

- Large LCD display provides easy-to-read numbers
- Precision adjustments for accurate measurements
- Hardened stainless steel head and body
- Lock screw to hold slide in position
- Linear accuracy: +/- .001" (.03 mm)
- Inch/millimeter conversion
- Zero at any position
- ON/OFF button
- Includes: Two 1.5 V batteries, type LR44 and deluxe storage case with foam inserts



**aurora tools**

Model No.	Size	Measurement Range	Approximate Jaw Depth	Price/Each
TGZ370	6	0-6" (152 mm)	1 9/16" (40 mm) outside, 13/16" (21 mm) inside	
TJZ861	8	0-8" (200 mm)	1 13/16" (46 mm) outside, 1" (26 mm) inside	
THZ769	12	0-12" (300 mm)	2 3/8" (60 mm) outside, 1" (26 mm) inside	

## 6" ELECTRONIC DIGITAL CALIPERS

- Large LCD display provides easy-to-read numbers
- Precision adjustments for accurate measurements
- ABS plastic head and stainless steel body
- Lock screw to hold slide in position
- Approximate jaw depth: 1 9/16" (40 mm) outside, 13/16" (21 mm) inside
- Inch/millimeter conversion
- Zero at any position
- Automatic shut OFF
- Includes two 3.0 V batteries, type CR3032 and a deluxe storage case with foam insert



**aurora tools**

Model No.	Measurement Range	Resolution	Price /Each
TLV181	0-6" (0-152 mm)	0.001" (0.03mm)	

## ABS DIGIMATIC CALIPER

- Digital readout LCD shows inch or metric units for versatility when measuring
- Advanced onsite sensor (AOS) electromagnetic inductive sensor for resistance to dirt, oil, and water
- Measures inside, outside, depth, and step values for versatility
- Includes protective case and SR44 silver oxide battery



**Mitutoyo**

Model No.	Mfg. No.	Measuring Range	Resolution	Accuracy +/-	Price /Each
HM704	500-196-30	0"-6" (0 mm-152 mm)	0.0005" (0.01 mm)	0.001" (0.0254 mm)	