

## 12" DOUBLE BEVEL SLIDING COMPOUND MITER SAWS



- Integrated XPS cross cut positioning system provides adjustment-free cut line indication for better accuracy and visibility
- Powerful 15 amp motor delivers extended power and durability
- Super efficient dust collection system captures over 75% of dust generated
- Exclusive back fence design cuts up to 2 x 16 dimensional lumber at 90° and 2 x 12 at 45°
- Adjustable stainless steel miter detent plate with 10 positive stops
- Dual horizontal steel rails with innovative clamping mechanism and linear ball bearings
- Innovative gearbox and belt-drive design increases vertical cutting capacity
- Includes: Carbide blade, blade wrench, dust bag & vertical material clamp

**Model No. TLV876**  
**Mfg. No. DWS780**  
**Price/Each \$**

### SPECIFICATIONS

**Voltage:** 120  
**Amperage:** 15.0  
**Arbor:** 5/8" or 1"  
**Mitre Range:** 50° Left and 60° Right  
**Tool Weight:** 56.0 lbs.



## 5 3/4" M18 FUEL™ DUAL BEVEL SLIDING COMPOUND MITER SAW KITS



- Includes: (1) M18™ REDLITHIUM™ HIGH DEMAND™ 9.0 battery pack, (1) blade wrench, (1) carbide tipped blade, (1) clamp, (1) dust bag
- Brushless motor runs cooler, lasts longer and delivers up to 55% faster application speed
- Cam locking miter system with adjustable stainless steel miter detent plate and 11 detent locations
- Up to 400 cuts per charge

**Model No. TYX086**  
**Mfg. No. 2734-21HD**  
**Price/Each \$**

### SPECIFICATIONS

**Voltage:** 18  
**Amperage:** 9.0  
**No Load RPM:** 4000  
**Mitre Range:** 50° Left to 60° Right  
**Bevel Range:** 48° Left to 48° Right  
**Tool Weight:** 45.0 lbs.



## 10" SLIDING COMPOUND MITRE SAWS W/LASER



- Twin laser guide system indicates the cut line on both sides of the blade kerf for reliable cuts every time
- Dual rail sliding system for sturdy, accurate and smooth sliding action
- Rotating table has nine positive stops at 0°, 15°, 22.5°, 30° and 45° right and left
- Includes: 2-position vertical hold down vise, retractable extension wings, dust bag and blade socket wrench

**Model No. TBS757**  
**Mfg. No. 8380**  
**Price/Each \$**

### SPECIFICATIONS

**Amperage:** 15.0  
**No Load RPM:** 5200  
**Arbor:** 5/8"  
**Mitre Range:** 45° Left to 45° Right  
**Bevel Range:** 45° Left to 0° Right  
**Tool Weight:** 40.0 lbs.



## 10" SLIDING DUAL COMPOUND MITRE SAWS W/LASER



- Twin laser guide system indicates the cut line on both sides of the blade kerf for reliable cuts every time
- Dual compound cuts (mitre and bevel) up to 45° left and right
- Dual rail sliding system for sturdy, accurate and smooth sliding action
- Rotating table has nine positive stops at 0°, 15°, 22.5°, 30° and 45° right and left
- Includes: 2-position vertical hold down vise, retractable extension wings, dust bag and blade socket wrench

**Model No. TLV733**  
**Mfg. No. 8385N**  
**Price/Each \$**

### SPECIFICATIONS

**Amperage:** 15.0  
**No Load RPM:** 5000  
**Arbor:** 5/8"  
**Mitre Range:** 45° Left to 45° Right  
**Bevel Range:** 45° Left to 0° Right  
**Tool Weight:** 42.0 lbs.



## 12" SINGLE BEVEL COMPOUND MITER SAWS



- Features stainless steel miter detent plate and cam miter lock
- Designed to provide repeatable accuracy and durability
- Features lightweight design and carrying handle for easy portability
- Includes: Compound miter saw, 12" carbide tipped blade, wrench, dust bag, and vertical clamp

**Model No. UAE025**  
**Mfg. No. DWS715**  
**Price/Each \$**

### SPECIFICATIONS

**Blade Diameter:** 12"  
**No Load RPM:** 4000 RPM  
**Amps:** 15 A  
**Voltage:** 120 V  
**Mitre Range:** 50° Left/50° Right  
**Bevel Range:** 48° Left/3° Right  
**Weight:** 36 lbs.



## 12" SLIDING DUAL COMPOUND MITRE SAWS W/LASER



- Twin laser guide system indicates the cut line on both sides of the blade kerf for reliable cuts every time
- Dual rail sliding system for sturdy, accurate and smooth sliding action
- Rotating table has nine positive stops at 0°, 15°, 22.5°, 30° and 45° right and left
- Includes: 2-position vertical hold down vise, retractable extension wings, dust bag and blade socket wrench

**Model No. TLY298**  
**Mfg. No. 8390N**  
**Price/Each \$**

### SPECIFICATIONS

**Amperage:** 15.0  
**No Load RPM:** 3600  
**Arbor:** 1"  
**Mitre Range:** 45° Left to 45° Right  
**Bevel Range:** 45° Left to 45° Right  
**Tool Weight:** 55.0 lbs.

