

2115TIMAX IMPACT WRENCH

- · Titanium hammer case and composite housing
- 7-vane motor delivers added power with less weight
- Finely tuned twin hammer impact mechanism and motor deliver more torque, durability, and efficiency
- Feather-touch trigger provides maximum control
- Max. Torque in Reverse: 300 ft-lbs.
- Drive Type: Square Hog-Ring



Model

BW352



15000

ULTRA-COMPACT AIR IMPACT WRENCH

- · Stubby 4.6" length and compact design gives you total
- control to get up, under, over, or around any tough job One-handed forward/reverse push button and 3-mode power regulator give you maximum control
- Drive Type: Square, Hog-Ring
- Nut-Busting Torque: 475 ft-lbs
- Blows Per Minute: 1350





4 CFM 2235TIMAX IMPACT WRENCH

Air

Consumption

- The high torque output of the powerful vane motor is optimized to increase safety and control over the tool
- Titanium hammer case is designed to be strong and durable

2115TIMAX

- Features patented quiet tool technology reducing sound levels
- Max. Torque in Reverse: 930 ft-lbs.
- Drive Type: Square Hog-Ring





2135QXPA IMPACT WRENCH

- · Light, quiet, and powerful design
- Drive Type: Square
- Max. Torque in Reverse: 780 ft-lbs.
- Torque (Forward): 700 ft-lbs.
- Torque (Reverse): 780 ft-lbs.



(R)
Ingersoll Rand

Model	Mfg.	Air	Air	Sound	Drive"	No Load	Price
No.	No.	Consumption	Inlet	Level (dBA)		RPM	/Each
UAE021	2135QXPA	5 CFM	1/4" NPTF	90.7	1/2	11000	

2145QIMAX IMPACT WRENCH

- · Titanium hammer case is designed to be strong and durable
- Finely tuned twin hammer impact mechanism and motor deliver more torque, durability, and efficiency
- Feather-touch trigger provides maximum control
- Max. Torque in Reverse: 1350 ft-lbs.
- · Drive Type: Square Hog-Ring and Thru-Hole





Ingersoll Ra							
Model No.	Mfg. No.	Air Consumption	Air Sound Inlet Level (dBA)		No Load Drive" RPM		Price /Each
NJT321	21450IMAX	8.5 CFM	3/8" NPT	107.3	3/4	7000	

2925 SERIES IMPACT WRENCH

- · Bronze endplates and a corrosion preventative treatment prevents internal rust in outdoor, wet environments
- Choice of reverse bias or non-biased motors gives you solutions for both removing or fastening bolts
- Pressure-fed mechanism lubrication ensures complete
- · Weight: 12.2 lbs.
- Length: 9
- Configuration: Pistol
- · Free Speed Sound Level Pressure: 99.6





3900 SERIES IMPACT WRENCHES

- Thanks to the bronze end-plate and a corrosion preventative treatment, this series is corrosion and wear resistant, making it great for outdoor conditions
- The titanium hammer case and metal housing means this tool can withstand even the harshest conditions
- Twin hammer mechanism ensure consistent power and balance









Model	Mfg.	Air	Air	Sound		No Load	Forward	Blows	Weight		Price
No.	No.	Consumption	Inlet	Level (dBA)	Drive	RPM	Torque	Per Minute	lbs.	Length"	/Each
UAE350	3940B2TI	64	1/2" NPT	114.4	1"	6000	1650 ft-lbs.	800	21.2	13.5	
IIAF353	3955R2TI	80	1/2" NPT	112 5	1-1/2"	2750	3900 ft-lhs	700	34.6	16.5	