AIR TOOLS

AIR SCRIBE® PENS

Vibration level: 4.2 m/s²

INCLUDED ACCESSORIES:

- Air hose 3/16" (5 mm) I.D.
- Air filter assembly
- Stylus carbide tipped for writing and engraving •
- Anvil for use with chisels and blank
- Flat chisel for scaling and deburring
- Chisel blank, customized to suit
- Round nose chisel for cleaning weld beads
- Carrying case



Model No.	Mfg. No.	Max Blows Per Minute	Weight Ibs. kg	Length in. mm	Air Flow L/s CFM	Min Hose Bore in. mm	Sound Level dBA	Price /Each
AIR SCRIBE® KIT								
TCW246	CP9361-1 KIT	13 500	0.31 0.14	5 127	0.5 1.1	3/16 5	79	
TKZ813	P054177			Replacement Stylus				

COMPACT ENGRAVING PENS

- Finger tip start valve
- Fine point stylus
- Enhanced control
- Compact and lightweight
- Engraves at 32 400 BPM Quiet operation @ 59 dB(A)
- Model No. THZ727 Mfg. No. CP9160 Price/Each \$



DOTCO

rice

ach

10-04 SERIES -PRECISION PENCIL GRINDERS

- Tool weight: 0.2 lbs. Tool length: 5.8"
- Motor power: 0.1 HP (0.074 kW)
- Industrial bearing provides long life expectancy
- Designed for precision deburring and metal removal Compact and light aluminum weight housing
- Roll throttle equipped Tool requires lubricated airline at 90 PSI maximum
- Air consumption: 9 CFM
- Air inlet: 1/8" Sound level (dBA): 78 Collet size: 1/8" No load RPM: 60 000
- Model No. TYL565

Mfg. No. 10R0401-18 Price/Each \$

12-10 SERIES -**INLINE COLLET GRINDERS**

- Tool weight: 0.8 lbs.
- Tool length: 6.0"
- Motor power: 0.3 HP (0.22 kW)
- Abrasive capacity: 1/2" carbide burr or 1" mounted wheel
- Durable and ergonomic composite housing
- Compact size for ultimate control easy access to confined areas
- Ideal for die and mold work as well as deburring
- Standard equipped with lock-off lever
- Performance rated @ 90 PSI / 620 kPa air pressure
- Air consumption: 16 CFM
- Air inlet: 1/4' •
- Sound level (dBA): 81 .
- Collet size: 1/4"
- No load RPM: 25000

 NO 1040 	I KP/WI: 23 000	DUIU			
Model	Mfg.	Exhaust	P		
No.	No.	Location	/E		
TYL601	12L1003-36	Front			
TYL620	12L1082-36	Rear			

PENCIL GRINDERS 60 000 RPM

· High-speed air motor, controlled with patented governor, provides constant speed under load

TGZ034

51700

1/8"

8 SCFM 66 dB(A) Oil-Less Turbine 60 000 RPM Metal Rear 0.6 lbs

> 16lbs \$

- Precision, high-tolerance, low run-out collet.
- Run-out is a true 0.0002 @ 1" (25 mm) from face Super flexible hose for maximum agility

Model No.
Mfg. No.
Collet Insert Size:
Air Flow Rate @ 90 PSI:
Sound Level:
Motor Characteristic:
Free Speed:
Bearing Type:
Exhaust Type:
Weight:
Packaged Weight:
Price/Each:

15Z SERIES -**AIR MARKING PEN**

- Tool weight: 0.3 lbs.
 Tool length: 5.5"
- Free speed: 20 000 RPM
- Abrasive capacity: 1/8" stylus
- Motor power: 0.06 HP (0.044 kW)
- · Sliding sleeve throttle
- · Ideal for marking a variety of materials, ranging from aluminum to titanium
- Carbide tipped stylus
- · Engineered for heavy duty applications in the most demanding environment
- Air consumption: 9 CFM Air inlet: 1/4" Sound level (dBA): 80
- Model No. TYN251

Mfg. No. 15Z-710 Price/Each \$

10-90 SERIES -PRECISION TURBINE GRINDERS

DOTCO

DOTCO

- Tool weight: 0.5 lbs.
 Tool length: 5.4"
- Motor power: 0.06 HP (0.044 kW) Requires no air line lubrication - High precision ball bearings for long life expectancy
- Two-stage turbine motor with roll throttle
- Achieves a superb finish with its high speed and precision spindle
- Lightweight and durable aluminum housing
- Low vibration and quiet operation minimizes operator fatigue CAUTION: Use dry air at 90 PSI maximum: Do not
- lubricate turbine grinders. Lubrication will be detrimental to the operation and life of turbine tools Air consumption: 6 CFM • Air inlet: 1/8'
- Sound level (dBA): 75 Collet size: 1/8"
- No load RPM: 100000
- Model No. TYL572 Mfg. No. 10R9000-08

Price/Each \$

DOTCO

DYNABRADE

TOOLS & EQUIPMENT

TYL601