

CHEMICALS



RED & REDI MULTI-PURPOSE RED GREASE

- Delivers excellent lubrication
- Prevents rust, corrosion and oxidation
- Remains effective at extremely high temperatures
- Reduces friction and vibration
- Resists shock
- Red colour allows easy visual inspection
- Penetrates quickly
- Non-melting



Model No.	Mfg. No.	Size	Price /Each
AA873	C05816	11 oz.	

WHITE LITHIUM GREASE W/PTEF

- Rapidly forms into a pure white grease
- Heat and water resistant
- Produces a long lasting, protective film against rust and corrosion
- White colour allows easy visual inspection
- Does not contain any chlorinated solvents
- Accepted for use in Canadian food processing facilities



Model No.	Mfg. No.	Size	Price /Each
AA914	C03816	10 oz.	

LU100 WHITE LITHIUM GREASE

- Inhibits corrosion on unpainted metal surfaces
- High-solids, non-staining white grease
- Excellent for metal-to-metal applications
- Will not drip or run on vertical surfaces
- Effective from -20°F to 275°F
- For chains, gears, drives, hinges and other vertical or overhead surfaces
- Recommended for use on knock-out pins on mould equipment
- NSF registered category code H2



Model No.	Mfg. No.	Size	Price /Each
AA103	SC0100000	11 oz.	

VIPERLUBE™ HIGH PERFORMANCE SYNTHETIC GREASE

- Grease provides superior protection against equipment exposed to a wide range of operating temperatures and environments
- Use as a lubricant and protective anti-rust film on bearings, machine parts, equipment, or as a release agent on gaskets and seals
- Temperature resistance: 400°F (204°C) continuous
- NLGI Grade: 2/Severe Duty GC-LB
- NSF registered category code H1
- Accepted for use in Canadian food processing facilities



Model No.	Mfg. No.	Size	Price /Each
AB505	457456	3 oz.	
AB508	457457	14 oz.	
AB507	457458	400 g.	
AE853	1906102	10.1 oz.	
AB509	459782	30 lbs.	

DIELECTRIC GREASE

- Moisture proof barrier that lubricates and protects electrical equipment from salt, dirt, and corrosion
- High dielectric strength
- Good thermal, oxidation and chemical stability
- Temperature resistance: 400°F (204°C) continuous



Model No.	Mfg. No.	Size	Price /Each
AC365	270640	0.33 oz.	

WHITE LITHIUM GREASE

- For metal-to-metal and metal-to-plastic applications
- Corrosion protection
- No ODC's
- Temperature resistance: 380°F (193°C) dropping point



Model No.	Mfg. No.	Size	Price /Each
AA611	270638	1.5 oz. tube	
AE854	1906122	10.75 oz. Aerosol	

CLEAR PENETRATING GREASE

- Protects against corrosion
- Resists water washout
- Quick penetrating action
- High tack
- Metal detectable plastic components-DETEX™



Model No.	Mfg. No.	Size	Price /Each
AD479	C06716	11 oz.	

MULTI-PURPOSE CONCRETE REPAIR & ADHESIVE

- Excellent for bridging horizontal or vertical cracks, even under water
- Twice as strong as concrete
- Works on concrete, masonry, brick, steel and more
- For indoor or outdoor use
- Colour: Light Gray



Model No.	Mfg. No.	Size	Price /Each
KP497	257395	9 oz.	
KP498	257397	Replacement Static Mixers - 3 Pack	

TURBOKRETE CONCRETE PATCH COMPOUND KITS

- Easily repair deep holes and cracks
- 100%-solids epoxy patch kit is designed for floors exposed to heavy traffic and intermittent chemicals
- Protects against abrasion, impact and most chemicals—no sealer required
- Creates an extremely hard surface—3-4 times stronger than concrete
- For interior/exterior use on damaged or severely spalled floors, curbs, ramps, etc.
- Odorless
- Easy-mix kit includes base, activator and aggregate
- Colour: Light Gray



Model No.	Mfg. No.	Size	Price /Each
KP495	253479	2 gal.	
KP496	5494323	3.5 gal.	